

*B2
(concl.)
Sub
Cant*

different areas, wherein said different areas are nominally aligned along a horizontal line; and

examining the diagnostic pattern to determine whether the accumulated media advance error is sufficiently objectionable to take corrective action.

*Sub
Cant
B3*

8. (Amended) A diagnostic method for visual detection of poor media advance calibration in an ink-jet printing system, comprising:

printing different areas of a diagnostic pattern at different passes of one or more ink-jet printheads with a controlled amount of media advances between the passes, to accumulate media advance error between the printing of the different areas, said printing different areas of a diagnostic pattern comprising applying a diagnostic multi-pass print mode mask, wherein a plurality of carriage passes are employed to print the area subtended by a printhead nozzle array, the diagnostic print mode mask comprising a rectilinear grid of pixels, and wherein said different areas include a first set of pixels on a row of said grid, and a second set of pixels on said row, and wherein said first set of pixels is printed on a different pass than said second set of pixels is printed, and wherein said diagnostic print mode mask defines that the first $w/2$ pixels in the row are printed in the same pass (a_i), and the last $w/2$ pixels in the row are printed in another pass (b_i); and

examining the diagnostic pattern to determine whether the accumulated media advance error is sufficiently objectionable to take corrective action.

*Sub
Cant
B4*

10. (Amended) A diagnostic method for visual detection of poor media advance calibration in an ink-jet printing system, comprising:

providing an ink-jet printhead mounted on a carriage, the carriage mounted for movement along a scan axis;

providing a media advance system for advancing a print medium along a media path which is transverse to the scan axis;

entering a diagnostic multi-pass print mode in which mode normal printing jobs of the printing system are not printed;

printing different areas of a diagnostic plot at different passes using said ink-jet printhead with a controlled amount of media advances between the passes to accumulate media advance error between the printing of the different areas; and

BH
(copy)
Sub C
BS

examining the diagnostic plot to determine whether the accumulated media advance error is sufficiently objectionable to take corrective action.

Sub C
BS

15. (Amended) A diagnostic method for visual detection of poor media advance calibration in an ink-jet printing system, comprising:

providing an ink-jet printhead mounted on a carriage, the carriage mounted for movement along a scan axis;

providing a media advance system for advancing a print medium along a media path which is transverse to the scan axis;

entering a diagnostic multi-pass print mode;

checking for printhead health and taking any corrective needed action prior to printing a diagnostic pattern;

printing different areas of the diagnostic plot at different passes using said ink-jet printhead with a controlled amount of media advances between the passes to accumulate media advance error between the printing of the different areas; and

examining the diagnostic plot to determine whether the accumulated media advance error is sufficiently objectionable to take corrective action.

Sub C
BS

17. (Amended) A diagnostic method for visual detection of poor media advance calibration in an ink-jet printing system, comprising:

providing an ink-jet printhead mounted on a carriage, the carriage mounted for movement along a scan axis;

providing a media advance system for advancing a print medium along a media path which is transverse to the scan axis;

entering a diagnostic multi-pass print mode;

printing different areas of a diagnostic plot at different passes using said ink-jet printhead with a controlled amount of media advances between the passes to accumulate media advance error between the printing of the different areas, said printing different areas of a diagnostic plot comprising applying a diagnostic multi-pass print mode mask, wherein a plurality of carriage passes are employed to print the area subtended by a printhead nozzle array, the diagnostic print mode mask comprising a rectilinear grid of pixels, and wherein said different areas include a first set of pixels on a row of said grid, and a second set of pixels on said row, and wherein said first set of pixels is printed on a different pass than said second set of pixels is printed, wherein said diagnostic print